

MAXI-FLEX

2 K POLYESTER PUTTY FOR PLASTICS

Edition: 022 2014/04

Cod: 5214007024.00000.022

APPLICATION

MASI-FLEX is a flexible Polyester Putty specially developed to repair plastic bumpers in cars: PC, PC-PBT, PP-EPDM. Outstands for its easy application, great filling power in dents and scratches, excellent sanding and fineness.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,85 ± 0,05
Grinding Fineness (μ)	Without lumps
Supply viscosity at 20°C	Thixotropic
%Solids content (weight / volume)	89 % ± 2 weight; (Mixture with hardener)
V.O.C. (g/l)	< 250 (Ready to use) - (2004/42/CE) IIB (B) (250)
Type of product	Polyester
Colour	Grey 7024

SURFACE PREPARATION

The surface must be dry, free from dirt and thoroughly degreased. Previous sanded is recommended. It may be repainted with any top coat once sealed with BESA-CAR or BESA-EXPRESS.

APPLICATION INSTRUCTIONS

Application: Spatula.

Note: Do not add too much hardener to avoid bleedings.



E-39
2-3 % weight



Pot-life 3-5'



1000-3000 my



30'



5'



P-120
P-220

FEATURES OF DRY FILM

Theoretical yield (m ² /l)	
Gloss 60°-60°	Matt
Second layer	1 - 2 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended. Can life: **12 months** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.