



TECHNICAL DATA SHEET

VIA MASULLO 1^ TRAV.PRIVATA 80010-QUARTO-(NA)-ITALY
 TAL.+ 39 - 081 - 876.21.48 r.a. - FAX + 39 - 081 - 876.23.47
<http://www.dichem.it> E-mail: dichem@dichem.it

CODE: 36.335

ACRILUX 2K VOC 420 PLUS

DESCRIPTION

2K high solid clear acrylic topcoat VOC 420 g/Lt compliant to European Dir. 2004/42/CE
 High gloss retention, excellent flow properties, perfect surface hardness and exceptional good finishing results.
 The well applied film coat will show perfectly spread like it is "mirror coated" without using polish and abrasive paste.

PURPOSE

All types of refinishing after touching-up or complete respray on normal or metallic automotive colours.

COLOURS

Transparent

BASIC DATA (At 25 deg. C - 50 % R. H.)

COVERAGE THEORETICAL

7,7 sqm/mixed litre (dft 50 um)

V.O.C. (g/Lt.) 2004/42/CE

420,00

HARDENER

Unihard 600

THINNER

Diacril

**MIXING RATIO BY VOLUME
2 : 1**

Acrilux 2k VOC 420 Plus	volume 100 cc	weight 100 gr
Unihard 600	50 cc	50 gr
Diacril	0-5 %	0-5%

POT-LIFE

3 hours with slow hardener
 2 hours with standard hardener
 1 hour with fast hardener

