



TECHNICAL DATA SHEET

VIA MASULLO 1^ TRAV.PRIVATA 80010-QUARTO-(NA)-ITALY
TAL.+ 39 - 081 - 876.21.48 r.a. - FAX + 39 - 081 - 876.23.47
<http://www.dichem.it> - E-mail: dichem@dichem.it

TECHNICAL DATA SHEET

PRODUCT: PRIMER FOR PLASTIC

CODE: DS810

PROPERTIES AND AREAS OF USE: Acrylic paints with excellent adhesion: to metals and to plastic, wood and ceramic materials to favour the adhesion of other top coat paints which have difficulty adhering to certain surfaces, such as polycarbonate, polypropylene and similar materials.

The 400 ml can covers an area of 1.5 - 2 m², depending on the type of element to be painted.

SUPPLY SPECIFICATIONS:

15 bar foil-coated can

Net content

Appearance

Colour

Scent

Density at 20°C

Pressure at 20°C

Pressure at 50°C

Flammability point

Viscosity Ford Cup 4

Remaining dry cylinder

Grit to grindometro

Gloss

Thickness 1 hand

Thickness 3 hands

Temperature resistance

Drying time:

Dust resistant

Dry to touch

Fully dry

May be painted over at any time

Childproof patented safety cap

Colour reference patch

400 ml

Can containing pressurized liquid

Miscellaneous

Typical solvent

0.75 - 0.80 g/ml

4.0 ± 0.5 bar

8.0 ± 0.5 bar

less than 0° C

11,5''

22%

From 0 to 2 Micron

15 Gloss

12 Micron

35 - 40 Micron

100 - 120°C

10 minutes

20 minutes

24 hours

LABELLING:



Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.