



TECHNICAL DATA SHEET

VIA MASULLO 1^ TRAV.PRIVATA 80010-QUARTO-(NA)-ITALY
TAL.+ 39 - 081 - 876.21.48 r.a. - FAX + 39 - 081 - 876.23.47
<http://www.dichem.it> - E-mail: dichem@dichem.it

TECHNICAL DATA SHEET

PRODUCT: PRIMER FILLER DARK GREY/LIGHT GREY

CODE: DS830/DS840

PROPERTIES AND AREAS OF USE: For filling small scratches and imperfections. Suitable for bodywork or metal surfaces. Rub over with very fine sandpaper before repainting, if necessary. The 400 ml can covers an area of 1.5 - 2 m², depending on the colour of the paint.

SUPPLY SPECIFICATIONS:

15 bar foil-coated can

Net content

400 ml

Appearance

Can containing pressurized liquid

Colour

Miscellaneous

Scent

Typical solvent

Density at 20°C

0.75 - 0.80 g/ml

Pressure at 20°C

4.0 ± 0.5 bar

Pressure at 50°C

8.0 ± 0.5 bar

Flammability point

less than 0° C

Viscosity Ford Cup 4

11,5''

Remaining dry cylinder

22%

Grit to grindometro

Da 0 a 2 Micron

Gloss

15 Gloss

Thickness 1 hand

12 Micron

Thickness 3 hands

35 - 40 Micron

Temperature resistance

100 - 120°C

Drying time:

Dust resistant

10 minutes

Dry to touch

20 minutes

Fully dry

24 hours

May be painted over at any time

Childproof patented safety cap

Colour reference patch

LABELLING:

Directive 2004/42/CE: C.O.V.

Subcategory: Special finishes

COV value limit: 840 g/Litre

Max. actual contents: 640 g/Litre



Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.