



# TECHNICAL DATA SHEET

VIA MASULLO 1^ TRAV.PRIVATA 80010-QUARTO-(NA)-ITALY  
TAL.+ 39 - 081 - 876.21.48 r.a. - FAX + 39 - 081 - 876.23.47  
<http://www.dichem.it> - E-mail: [dichem@dichem.it](mailto:dichem@dichem.it)

## TECHNICAL DATA SHEET

**PRODUCT: SILVER FOR WHEEL**

**CODE: DS920**

**PROPERTIES AND AREAS OF USE:** Special fast-drying acrylic paint with high resistance to atmospheric agents. The quality of the substances used ensures the stability of the colours in time and repetition of the original colours, for retouching cars, motorbikes, scooters and bicycles. It withstands the effects of any fuel spillage. High-gloss finishes are obtained, with good resistance to rubbing and polishing. The 400 ml can covers an area of 1.5 - 2 m<sup>2</sup>, depending on the colour of the paint.

### SUPPLY SPECIFICATIONS:

15 bar foil-coated can

Net content

Appearance

Colour

Scent

Density at 20°C

Pressure at 20°C

Pressure at 50°C

Flammability point

Viscosity Ford Cup 4

Remaining dry cylinder

Grit to grindometro

Gloss

Thickness 1 hand

Thickness 3 hands

Temperature resistance

Drying time:

Dust resistant

Dry to touch

Fully dry

May be painted over at any time

Childproof patented safety cap

Colour reference patch

400 ml

Can containing pressurized liquid

Miscellaneous

Typical solvent

0.75 - 0.80 g/ml

4.0 ± 0.5 bar

8.0 ± 0.5 bar

less than 0° C

From 11'' to 11,5''

From 12,4% to 17,2%

From 0 to 2 Micron

From 15 to 85 Gloss

7 - 10 Micron

20 - 30 Micron

100 - 130°C

10 minutes

20 minutes

24 hours

### LABELLING:



Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product