

POLYFILL

Body filler polyester 2K universal



Two component Universal Body filler by spatula application, fast drying time, it is used for fast repair in large surfaces for car and industry

Soft

Low Specific weight

Extremely fine







Easy to spread

Excellent sanding

Perfect adhesion on Zinc surface

Resistant to high temperatures

POLY FILL – Body filler polyester 2K universal

	1-3% with PEROXIDE OF BENZOYLE according to the temperature : <math><5-10^{\circ}\text{C}</math>: 3% 10-20°C: 2% 20- 30°C: 1%
	Mixing ratio: 100:1>3
	Mix and apply the product with the spatula
	By air: 15-30mm (according to temperature and to the quality of the hardener)
	Dry sanding by P80 – P120 Refinishing by P180 – P240 – P320
	It is suggested to wear protective clothing even if not required.

COLOR:

WHITE – Other colours upon demand (**for a minimum quantity**)

SUPPORTS/USE:

used for both car body and industrial repair of steel, galvanized and aluminium sheets. Perfect adhesion also on plastic and wood surfaces.

SPECIFIC WEIGHT: 1.0 kg/l

STORAGE: 12 months in sealed cans and stocked in dry place at temperature between + 5° and + 30° C far from hot sources.

PROFESSIONAL USE ONLY