



TECHNICAL DATA SHEET

VIA MASULLO 1^ TRAV.PRIVATA 80010-QUARTO-(NA)-ITALY
 TAL.+ 39 - 081 - 876.21.48 r.a. - FAX + 39 - 081 - 876.23.47
<http://www.dichem.it> - E-mail: dichem@dichem.it

CODE: 35.140

POLYSTUK PLATINUM PLUS

DESCRIPTION

Polyester filler VOC compliant by spatula application, medium pot-life formulated for the repairing of large surfaces **VERY SUITABLE FOR GALVANISED PLATE**. Excellent sanding, easy to spread and high filling properties.

PURPOSE

To use as filler for the repairing of sheet in car and industrial body-work as for industrial coatings (steel, wood, hard plastic, fibertix etc...).

COLOURS

Light Yellow
 Others colours upon request (subject to minimum quantity)

BASIC DATA (At 20 deg. C - 50 % R. H.)

VOC content

250 g/Lt

HARDENER

PEROXIDE OF BENZOYLE 50%

**MIXING RATIO: 3-2-1%
 According to the
 temperature**

	< 5-10°C	10-20°C	20-30°C
Polystuk:	100	100	100
Peroxide of benzoyle 50%	3	2	1

POT-LIFE

12-8 min. 8-5 min. 5-3 min.

<p>APPLICATION METHOD</p> <p>DRYING TIMES BY AIR</p> <p>SANDING</p>	<p>By spatula</p> <p>30 Minutes</p> <p>After 15 – 30 minutes at 20°C</p> <p>Dry sanding by P80 and refinishing by P120 and P240</p>
<p>STORAGE</p>	<p>12 months (stored in a cool dry place away from direct sunlight).</p>
<p>PACKAGING</p> <p>CARTON</p>	<p>Kit 1 Kg gross weight including hardener's tube 20 gr.</p> <p>Kit 2 Kg gross weight including hardeners's tube 40 gr.</p> <p>Kit 5 Kg gross weight including hardener's tube 100 gr.</p> <p>18 x 1 kg Kit - 8 x 2 kg Kit – 4 x 5 kg Kit</p>

Our technical department is at your service for any further details or information you may require.